



CONCRETE SHIELD

Concrete, Brick, Masonry & Exposed Aggregate Sealer

Why Concrete Shield?

Use on Stamped and Colored Concrete • Provides Years of the Highest Quality Protection • Resistant to Gas & Oil and Commercial Chemicals Enhances and Protects the Clean Natural Look of Concrete • UV Stable

Description

Concrete Shield is a thermoplastic, all acrylic polymer which forms a long lasting, waterproofing seal on concrete, brick, masonry, aggregate and stone. For pavers see Interlock's Paver Shield. Concrete Shield's unique formulation protects against the sun's UV rays, gasoline, commercial chemicals, deicing salts and oils. This sealer protects the clean natural look of the surface for years.

Features

- Water Repellant
- Retards Efflorescence
- Easy application
- High degree of resistance to commercial chemicals
- Unaffected by commercial de-icing salts

Benefits

- Maintains performance life of pavement
- Reduces interim maintenance
- VOC compliant and UV stable
- Enhances color of stained concrete/masonry




CONCRETE SHIELD

Concrete, Brick, Masonry & Exposed Aggregate Sealer

How It Works

Concrete Shield seals the capillaries of the concrete, protecting it against harmful chemicals and stains, while still allowing it to breathe.



Application

- 1 Remove all oil, dirt, debris and efflorescence prior to sealing and let dry.
- 2 Ensure that Concrete Shield is only applied when there is no risk of rain within the next 6 hours.
- 3 Do not apply in extremes of temperature (below 40 F or above 110 F).
- 4 Apply to surface of concrete liberally and spread all surpluses with a heavy nap roller. A low pressure garden type sprayer may be used to apply Concrete Shield. Back brushing is recommended.
- 5 Accurate application rates are critical (typically 150 – 200 sq ft per gallon). Do not thin.
- 6 Avoid walking on the sealed area for 2 hours after application and do not drive motor vehicles on the surface for 24 hours.
- 7 ALWAYS WEAR PROTECTIVE GLOVES AND GOGGLES. NO SMOKING. WEAR A MASK WHEN WORKING IN CONFINED AREAS. Please refer to current MSDS.
- 8 All uncured spillages/splashes, and all tools must be cleaned immediately. Use warm soap and water for cleanup.

APPLICATION NOTE: It is recommended that you test a small area to assure satisfaction of appearance.

First Aid

If swallowed, give large quantities of water to dilute and call a physician. In case of eye contact, rinse immediately with water for 15 to 20 minutes. For skin contact, wash thoroughly with soap and water.
KEEP FROM FREEZING - KEEP OUT OF REACH OF CHILDREN

Warranty

Manufacturer warrants its products conform to the published specifications. No other warranty is expressed or implied. The user must determine the suitability of the products for their particular use. Manufacturer and any seller's liability for incidental or consequential damages hereunder shall not exceed the purchased price of the product used.



7186 W. Gates Ave. Salt Lake City, UT 84128
877.655.8855 FAX 801.987.4101 www.interlockpro.com

The Interlock Guarantee: Interlock Professional Products guarantees your satisfaction with the application and performance properties of this product if it is correctly applied to a properly prepared surface in accordance with label directions. Specifically, Interlock warrants this product will prevent water damage and graying of the substrate for 10 years after the date of purchase. This warranty does not cover wood that has water damage prior to sealant application and graying due to surface mildew growth. If you are not completely satisfied with this product's performance, Interlock will provide replacement product or refund the purchase price – Guaranteed. LABOR AND ALL OTHER DIRECT, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. INTERLOCK MAKES NO OTHER EXPRESS WARRANTIES. To make a claim under this warranty, supply proof of purchase to the store where you purchased the product or contact: Interlock Professional Products, 7186 W. Gates Ave, West Valley City, UT 84128